



Part Number : [1200062799](#)

Product Description : Micro-Change (M12) Single-Ended Cordset, 5 Poles, Male (Straight) to Pigtail, 0.34mm<sup>2</sup> PVC Cable, 1.0m (3.28') Length

Series Number : 120006

Status : Active

Product Category : Circular Industrial Cordsets

Engineering Number : 805006E03M010



---

## Documents & Resources

### Drawings

[1200062799\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant  |
| China RoHS         |  |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21  |
| REACH SVHC         | Contains Lead... per D(2024)4144-DC (27 June 2024)                                    |
| EU RoHS            | Compliant with Exemption 6(c) per EU 2015/863   |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

|              |  |
|--------------|--|
| Status       | Active   |
| Category     | Circular Industrial Cordsets   |
| Series       | 120006   |
| Description  | Micro-Change (M12) Single-Ended Cordset, 5 Poles, Male (Straight) to Pigtail, 0.34mm <sup>2</sup> PVC Cable, 1.0m (3.28') Length |
| IP Rating    | IP67   |
| Product Name | Micro-Change (M12)   |
| Protocol     | N/A  |
| Type         | Single Ended   |
| UPC          | 883906138394   |

### Agency

|    |         |
|----|---------|
| UL | E152210 |
|----|---------|

### Electrical

|                               |            |
|-------------------------------|------------|
| Current - Maximum per Contact | 4.0A       |
| Voltage - Maximum             | 250V AC/DC |

### Physical

|                      |                    |
|----------------------|--------------------|
| Cable Diameter       | 5.80mm (.230")     |
| Cable Length         | 1.0m (3.28')       |
| Color - Cable Jacket | Black              |
| Connector End A      | Micro-Change (M12) |
| Connector End B      | Pigtail            |
| Coupling Style       | Threaded           |
| Gender               | Male-Pigtail       |
| Keyway               | Single             |
| LED Indicator        | None               |

|                               |                     |
|-------------------------------|---------------------|
| Material - Cable Jacket       | PVC                 |
| Material - Connector Body     | PUR                 |
| Material - Contact            | Copper Alloy        |
| Material - Coupling Nut       | Nickel-plated Brass |
| Material - O-Ring             | Fluoro-elastomer    |
| Material - Plating Mating     | Gold                |
| Orientation                   | Straight to Pigtail |
| Poles                         | 5                   |
| Temperature Range - Operating | -30° TO +80°C       |
| Wire/Cable Type               | UL 2464             |
| Wire Size (AWG)               | N/A                 |

---

This document was generated on Mar 27, 2025