



Part Number : [1200680190](#)

Product Description : Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male (Straight) to 2 x 3-Pole Female (Straight), 22 AWG PVC Cable, 1.0m Length

Series Number : 120068

Status : Active

Product Category : Industrial Tees and Splitters

Engineering Number : 884A30K03M010




Documents & Resources

Drawings

[1200680190_sd.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

| | |
|--------------|--|
| Status | Active |
| Category | Industrial Tees and Splitters |
| Series | 120068 |
| Description | Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male (Straight) to 2 x 3-Pole Female (Straight), 22 AWG PVC Cable, 1.0m Length |
| IP Rating | IP67 |
| Product Name | Micro-Change (M12) |
| Type | Splitter - In-line |
| UPC | 78678845021 |

Agency

| | |
|-----|---------|
| CSA | LR6837 |
| UL | E152210 |

Electrical

| | |
|-------------------------------|------------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 250V AC/DC |

Physical

| | |
|----------------------|--------------------|
| Color - Cable Jacket | Yellow |
| Drop Connector | N/A |
| Drop Gender | N/A |
| Keyway | Single |
| LED Indicator | None |
| Left Trunk Connector | Micro-Change (M12) |
| Left Trunk Gender | Male |
| Leg 1 Length | 1.0m |
| Leg 2 Length | 1.0m |

| | |
|-------------------------------|---------------------|
| Material - Cable Jacket | TPE |
| Material - Connector Body | TPE |
| Material - Coupling Nut | Nickel-plated Brass |
| Net Weight | 232.828/g |
| Poles | 3 Female/4 Male |
| Right Trunk Connector | Micro-Change (M12) |
| Right Trunk Gender | Female |
| Temperature Range - Operating | -30°C TO +80°C |

This document was generated on Mar 27, 2025