



Part Number : 1553212005

Product Description : Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(2.50mm²) with Green-Yellow Ground + 2x(2x1.00mm² with Braided Shield) / 4x(14 AWG) with Green-Yellow Ground + 2x(2x18 AWG with Braided Shield), 14.10mm (.555") Diameter, 500.0m (1640.42') Length, Orange

Series Number : 307965

Status : Active

Product Category : Industrial Cable

Engineering Number : 1X500M



Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Relevant
EU ELV	Not Reviewed per 2000/53/EC
Low-Halogen Status	Not Relevant
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Not Reviewed per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Industrial Cable
Series	307965
Description	Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(2.50mm ²) with Green-Yellow Ground + 2x(2x1.00mm ² with Braided Shield) / 4x(14 AWG) with Green-Yellow Ground + 2x(2x18 AWG with Braided Shield), 14.10mm (.555") Diameter, 500.0m (1640.42') Length, Orange
Geographic Area	Global
Product Name	Flamar,Servo Motor
UPC	889056460811

Agency

UL	E172949
----	---------

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	1000V

Physical

Bending Radius - Minimum	> 10xOD
Cable Length	500.0m
Circuits (Loaded)	8 (4+2+2)
Color - Cable Jacket	Orange
Insulation	TPE
Material - Outer Jacket	WSOR
Net Weight	0.320/kg
Outer Jacket Diameter	14.10mm
Packaging Type	Reel
Temperature Range - Operating	-25° to +80°C
Wire/Cable Type	UL AWM 21939 / CSA
Wire Size (AWG)	14, 18
Wire Size mm ²	1.00, 2.50

Use with Part(s)

Description	Part Number
Brad M23 Signal Connectors	<u>120230</u>
Brad M23 Signal Connectors	<u>120233</u>
