



Part Number : 1554216002

Product Description : Flamar Ethernet 5e Network Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.14mm²) / 2x(2x26 AWG), 6.50mm (.256") Diameter, 500.0m (1640.42') Length, Teal

Series Number : 307964

Status : Active

Product Category : Industrial Cable

Engineering Number : 1X500M



Product Environment Compliance

Compliance

| | |
|--------------------|--|
| GADSL/IMDS | Not Relevant |
| China RoHS | |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|--------|--------|
| Status | Active |
|--------|--------|

| | |
|-----------------|--|
| Category | Industrial Cable |
| Series | 307964 |
| Description | Flamar Ethernet 5e Network Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.14mm ²) / 2x(2x26 AWG), 6.50mm (.256") Diameter, 500.0m (1640.42') Length, Teal |
| Geographic Area | Global |
| Product Name | Flamar,Network |
| Protocol | EtherNet 5e |
| UPC | 889056464925 |

Agency

| | |
|----|---------|
| UL | E172949 |
|----|---------|

Electrical

| | |
|-------------------------------|---------------|
| Current - Maximum per Contact | Contact Molex |
| Voltage - Maximum | 600V |

Physical

| | |
|-------------------------------|--------------------|
| Bending Radius - Minimum | > 15xOD |
| Cable Length | 500.0m |
| Circuits (Loaded) | 4 |
| Color - Cable Jacket | Teal |
| Insulation | PE |
| Material - Outer Jacket | WSOR |
| Net Weight | 0.052/kg |
| Outer Jacket Diameter | 6.50mm |
| Packaging Type | Reel |
| Temperature Range - Operating | -10° to +60°C |
| Wire/Cable Type | UL AWM 21215 / CSA |
| Wire Size (AWG) | 26 |
| Wire Size mm ² | 0.14 |

Use with Part(s)

| Description | Part Number |
|---|---------------|
| Micro-Change (M12) Field Attachable Connectors | <u>120071</u> |
| Micro-Change (M12) Field Attachable Connectors and D-Sub Connectors | <u>120100</u> |
| Micro-Change (M12) and Mini-Change Trunk and Drop Connectors | <u>130034</u> |
| Field Attachable Connectors | <u>130047</u> |

This document was generated on Mar 27, 2025