



**Part Number :** [1200310046](#)

**Product Description :** Nano-Change (M8) Receptacle, 3 Poles, M8 x 1.0 Mounting Threads, Female (Straight) to 22 AWG Leads, 0.30m (11.81") Length

**Series Number :** 120031

**Status :** Active

**Product Category :** Circular Industrial Connectors

**Engineering Number :** 4R3H40E02C3003



---

## Documents & Resources


### Drawings

[1200310046\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## Part Details

### General

Status	Active
Category	Circular Industrial Connectors
Series	120031
Description	Nano-Change (M8) Receptacle, 3 Poles, M8 x 1.0 Mounting Threads, Female (Straight) to 22 AWG Leads, 0.30m (11.81") Length
IP Rating	IP67
NEMA Rating	NEMA 6
Product Name	Nano-Change (M8)
Type	Single Ended (pigtail)
UPC	883906177904

### Agency

UL	E152210
----	---------

### Electrical

Current - Maximum per Contact	3.0A
Voltage - Maximum	60V AC / 75V DC

### Physical

Coupling Type	Internal Thread
Gender	Female
Keyway	None
Length	0.30m
Material - Component	Nickel-plated Brass
Mounting Thread Size	M8 x 1.0
Net Weight	14.615/g
Orientation	Straight
Panel Mount	Back
Poles	3

Temperature Range - Operating	-25° to +90°C
Wire/Cable Type	Leads
Wire Size (AWG)	24

---

This document was generated on Mar 27, 2025