



**Part Number :** [1200656656](#)

**Product Description :** Micro-Change (M12) Single-Ended Cordset with Knurled Hexnut, 5 Poles, Female (Straight) to Pigtail, 22 AWG, Yellow TPU WSOR Cable, Yellow Overmold, 15.0m (49.21') Length

**Series Number :** 120065

**Status :** Active

**Product Category :** Circular Industrial Cordsets

**Engineering Number :** 805000B55M150Y



---

## Documents & Resources

### Drawings

[1200656656\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |  |
|--------------------|--|
| GADSL/IMDS         | Not Relevant                                   |
| China RoHS         | Not Relevant                                   |
| EU ELV             | Compliant with Exemption 3 per 2000/53/EC      |
| Low-Halogen Status | Not Relevant                                   |
| REACH SVHC         | Contains Lead per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS            | Compliant with Exemption 6(c) per EU 2015/863  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

|              |   |
|--------------|---|
| Status       | Active  |
| Category     | Circular Industrial Cordsets  |
| Series       | 120065  |
| Description  | Micro-Change (M12) Single-Ended Cordset with Knurled Hexnut, 5 Poles, Female (Straight) to Pigtail, 22 AWG, Yellow TPU WSOR Cable, Yellow Overmold, 15.0m (49.21') Length |
| IP Rating    | IP67  |
| Product Name | Micro-Change (M12)  |
| Type         | Single Ended  |
| UPC          | 193264203093  |

### Agency

|    |         |
|----|---------|
| UL | E152210 |
|----|---------|

### Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum             | 60V  |

### Physical

|                      |                    |
|----------------------|--------------------|
| Cable Diameter       | 5.50mm (.216")     |
| Cable Length         | 15.0m (49.21')     |
| Color - Cable Jacket | Yellow             |
| Connector End A      | Micro-Change (M12) |
| Connector End B      | Pigtail            |
| Coupling Style       | Threaded           |
| Gender               | Female-Pigtail     |
| Keyway               | Single             |
| LED Indicator        | None               |

|                               |                     |
|-------------------------------|---------------------|
| Material - Cable Jacket       | TPU                 |
| Material - Connector Body     | TPU                 |
| Material - Contact            | Brass               |
| Material - Coupling Nut       | Nickel-plated Brass |
| Material - O-Ring             | FPM                 |
| Material - Plating Mating     | Gold                |
| Net Weight                    | 124.000/g           |
| Orientation                   | Straight to Pigtail |
| Poles                         | 5                   |
| Temperature Range - Operating | -25° to +80°C       |
| Wire/Cable Type               | UL 21215            |
| Wire Size (AWG)               | 22                  |

---

This document was generated on Mar 27, 2025