



Part Number : [1200660035](#)

Product Description : Micro-Push (M12) Double-Ended Cordset, 4 Poles, A-Coded, Male (Straight)-to-Female (Straight), 22 AWG, Unshielded PVC Cable, 1.0m (3.28') Length

Series Number : 120066

Status : Active

Product Category : Circular Industrial Cordsets

Engineering Number : NN4030A41M010G



Documents & Resources

Drawings

[1200660035_sd.pdf](#)

Product Environment Compliance

Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120066
Description	Micro-Push (M12) Double-Ended Cordset, 4 Poles, A-Coded, Male (Straight)-to-Female (Straight), 22 AWG, Unshielded PVC Cable, 1.0m (3.28') Length
IP Rating	IP65
Product Name	Micro-Push
Type	Double Ended
UPC	78678852522

Agency

UL	E152210
----	---------

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Cable Diameter	4.70mm (.185")
Cable Length	1.0m (3.28')
Color - Cable Jacket	Black
Connector End A	Micro-Push (M12)
Connector End B	Micro-Push (M12)
Coupling Style	Push to Lock
Gender	Female-Male
Keyway	A-Coded
LED Indicator	None
Material - Cable Jacket	PVC
Material - Connector Body	Nylon
Material - Contact	Copper Alloy
Material - Coupling Nut	N/A

Material - Plating Mating	Gold
Orientation	Straight to Straight
Poles	4
Temperature Range - Operating	-25° to +105°C
Wire/Cable Type	Unshielded PVC
Wire Size (AWG)	22

This document was generated on Mar 27, 2025