



Part Number : [1200678308](#)

Product Description : Micro-Change (M12) Single-Ended Cordset, 3 Poles, Female (90°) to Pigtail with PNP Sensors, 0.34mm² PUR LSOH Cable 2.0m (6.56') Length

Series Number : 120067

Status : Active

Product Category : Circular Industrial Cordsets

Engineering Number : 8030P1H09M020




Documents & Resources

Drawings

[1200678308_sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120067
Description	Micro-Change (M12) Single-Ended Cordset, 3 Poles, Female (90°) to Pigtail with PNP Sensors, 0.34mm ² PUR LSOH Cable 2.0m (6.56') Length
IP Rating	IP67
Product Name	Micro-Change (M12)
Protocol	PROFIBUS
Type	Single Ended
UPC	78172514606

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	30V AC/DC

Physical

Cable Diameter	4.32mm (.170")
Cable Length	2.0m (6.56')
Color - Cable Jacket	Black
Connector End A	Micro-Change (M12)
Connector End B	Pigtail
Coupling Style	Threaded
Gender	Female-Pigtail
Keyway	Single
LED Indicator	PNP Sensors
Material - Cable Jacket	PUR
Material - Connector Body	PUR
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass

Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Orientation	90° to Pigtail
Poles	3
Temperature Range - Operating	-30° to +90°C
Wire/Cable Type	UL 21198
Wire Size (AWG)	N/A

This document was generated on Mar 27, 2025