



Part Number : [1200678329](#)

Product Description : Micro-Change (M12)
Double-Ended Cordset, 3 Poles, Female (90°)
to Male (90°) with PNP LED Sensors, 0.34mm²
PUR LS0H Cable, 1.0m (3.28') Length

Series Number : 120067

Status : Active

Product Category : Circular Industrial
Cordsets

Engineering Number : 8830P9H09M010



Documents & Resources

Drawings

[1200678329_sd.pdf](#)

Product Environment Compliance

Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120067
Description	Micro-Change (M12) Double-Ended Cordset, 3 Poles, Female (90°) to Male (90°) with PNP LED Sensors, 0.34mm ² PUR LS0H Cable, 1.0m (3.28') Length
IP Rating	IP67
Product Name	Micro-Change (M12)
Protocol	PROFIBUS
Type	Double Ended
UPC	78172555067

Agency

UL	E152210
----	---------

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	30V AC/DC

Physical

Cable Diameter	N/A
Cable Length	1.0m (3.28')
Color - Cable Jacket	Black
Connector End A	Micro-Change (M12)
Connector End B	Micro-Change (M12)
Coupling Style	Threaded
Gender	Female-Male
Keyway	Single
LED Indicator	PNP Sensors
Material - Cable Jacket	PUR
Material - Connector Body	TPU
Material - Contact	Copper Alloy

Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Orientation	90° to 90°
Poles	3
Temperature Range - Operating	-30° TO +80°C
Wire/Cable Type	UL 21198
Wire Size (AWG)	N/A

This document was generated on Mar 27, 2025