



Part Number : [1200680237](#)

Product Description : Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male (Straight) to 2 x 3-Pole Female (Straight), 18 AWG TPE Cable, 0.30m Length

Series Number : 120068

Status : Active

Product Category : Industrial Tees and Splitters

Engineering Number : 884A30A05M010



Documents & Resources

Drawings

[1200680237_sd.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|--------------|
| China RoHS | Not Reviewed |
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|--------------|---|
| Status | Active |
| Category | Industrial Tees and Splitters |
| Series | 120068 |
| Description | Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male (Straight) to 2 x 3-Pole Female (Straight), 18 AWG TPE Cable, 0.30m Length |
| IP Rating | IP67 |
| Product Name | Micro-Change (M12) |
| Type | Splitter - In-line |
| UPC | 78678890126 |

Agency

| | |
|-----|---------|
| CSA | LR6837 |
| UL | E152210 |

Electrical

| | |
|-------------------------------|------------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 250V AC/DC |

Physical

| | |
|---------------------------|---------------------|
| Color - Cable Jacket | Yellow |
| Drop Connector | Micro-Change (M12) |
| Drop Gender | Male |
| Keyway | Single |
| LED Indicator | None |
| Left Trunk Connector | Micro-Change (M12) |
| Left Trunk Gender | Female |
| Leg 1 Length | 1.0m |
| Leg 2 Length | 1.0m |
| Material - Cable Jacket | PVC |
| Material - Connector Body | PUR |
| Material - Coupling Nut | Nickel-plated Brass |

| | |
|-------------------------------|--------------------|
| Poles | 3 Female/4 Male |
| Right Trunk Connector | Micro-Change (M12) |
| Right Trunk Gender | Female |
| Temperature Range - Operating | -30°C TO +80°C |

This document was generated on Mar 27, 2025