



Part Number : [1200705208](#)

Product Description : Micro-Change (M12) Receptacle, 8 Poles, PG9 Mounting Threads, Female (Straight) to 0.25mm<sup>2</sup> PVC Leads, 0.30m (11.81") Length

Series Number : 120070

Status : Active

Product Category : Circular Industrial Connectors

Engineering Number : 8R8J20E02C3003




## Documents & Resources

### Drawings

[1200705208\\_sd.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Triphenyl-phosphate; Lead per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Circular Industrial Connectors
Series	120070
Description	Micro-Change (M12) Receptacle, 8 Poles, PG9 Mounting Threads, Female (Straight) to 0.25mm <sup>2</sup> PVC Leads, 0.30m (11.81") Length
IP Rating	IP67
NEMA Rating	NEMA 6
Product Name	Micro-Change (M12)
Type	Single Ended (pigtail)
UPC	884982224759

### Agency

CSA	LR6837
UL	E152210

### Electrical

Current - Maximum per Contact	2.0A
Voltage - Maximum	30V AC / 36V DC

### Physical

Coupling Type	Internal Thread
Gender	Female
Keyway	Single
Length	0.30m
Material - Component	Nickel-plated Brass
Mounting Thread Size	PG9
Net Weight	22.549/g
Orientation	Straight

Panel Mount	Front
Poles	8
Temperature Range - Operating	-25° to +90°C
Wire/Cable Type	Leads, UL 1061
Wire Size (AWG)	24

---

This document was generated on Mar 27, 2025