



Part Number : [1200710045](#)

Product Description : Micro-Change (M12)
Single Keyway with PG7 Cable Fitting, Straight
Male, 5 Poles, Cable Diameter 3.30-6.60mm

Series Number : 120071

Status : Active

Product Category : Circular Industrial
Connectors

Engineering Number : 8A5006-31



Documents & Resources

Drawings

[1200710045_sd.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|--|
| GADSL/IMDS | Not Relevant |
| China RoHS | |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|--------------|---|
| Status | Active |
| Category | Circular Industrial Connectors |
| Series | 120071 |
| Description | Micro-Change (M12) Single Keyway with PG7 Cable Fitting, Straight Male, 5 Poles, Cable Diameter 3.30-6.60mm |
| Approvals | cCSAus certified |
| IP Rating | IP67 |
| Product Name | Micro-Change (M12) |
| Type | Field Attachable Connector |
| UPC | 78678875705 |

Agency

| | |
|-----|--------|
| CSA | LR6837 |
|-----|--------|

Electrical

| | |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 30V AC / 36V DC |

Physical

| | |
|---------------------------|--------------------------|
| Cable Diameter | 3.30-6.60mm (.130-.260") |
| Coupling Type | External Thread |
| Diagnostics / LEDs | No |
| Diagnostics Port | No |
| Gender | Male |
| Keyway | Single |
| Material - Connector Body | PA |
| Material - Contact | Brass |
| Material - Coupling Nut | Nickel-plated Brass |

| | |
|-------------------------------|----------------|
| Material - Plating Mating | Silver |
| Net Weight | 25.500/g |
| Orientation | Straight |
| Poles | 5 |
| Temperature Range - Operating | -25°C to +90°C |
| Wire Size (AWG) | 18 |

This document was generated on Mar 27, 2025