



**Part Number :** [1200805067](#)

**Product Description :** Ultra-Lock (M12) Double-Ended Cordset, 4 Poles, Female (90°) to Male (Straight), 22 AWG, PUR/PVC Cable, 1.0m (3.28') Length

**Series Number :** 120080

**Status :** Obsolete

**Product Category :** Circular Industrial Cordsets

**Engineering Number :** WW4031P03M010



---

## Documents & Resources

---

### Product Environment Compliance

#### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Obsolete
Category	Circular Industrial Cordsets
Series	120080
Description	Ultra-Lock (M12) Double-Ended Cordset, 4 Poles, Female (90°) to Male (Straight), 22 AWG, PUR/PVC Cable, 1.0m (3.28') Length
IP Rating	IP68
Product Name	Ultra-Lock (M12)
Protocol	PROFINET
Type	Double Ended
UPC	884982225046

### Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	300V AC/DC

### Physical

Cable Diameter	5.30mm (.209")
Cable Length	1.0m (3.28')
Color - Cable Jacket	Black
Connector End A	Ultra-Lock (M12)
Connector End B	Ultra-Lock (M12)
Coupling Style	Push to Lock
Gender	Female-Male
Keyway	Single
LED Indicator	None
Material - Cable Jacket	PUR/PVC
Material - Connector Body	PUR
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Orientation	90° to Straight
Poles	4
Temperature Range - Operating	-30° TO +80°C

Wire/Cable Type	EU Cable
Wire Size (AWG)	22

---

This document was generated on Mar 27, 2025