



**Part Number :** [1200878136](#)

**Product Description :** Nano-Change (M8) Double-Ended Cordset, 3 Poles, Male (90°) to Female (Straight), 0.34mm<sup>2</sup> PVC Cable, with PNP LED Sensors, PVC Cable, 2.0m (6.56') Length

**Series Number :** 120087

**Status :** Active

**Product Category :** Circular Industrial Cordsets

**Engineering Number :** 4430P7E03M020



---

## Documents & Resources

### Drawings

[1200878136\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Reviewed per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Not Reviewed per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## Part Details

### General

Status	Active
Category	Circular Industrial Cordsets
Series	120087
Description	Nano-Change (M8) Double-Ended Cordset, 3 Poles, Male (90°) to Female (Straight), 0.34mm <sup>2</sup> PVC Cable, with PNP LED Sensors, PVC Cable, 2.0m (6.56') Length
IP Rating	IP67
Product Name	Nano-Change (M8)
Protocol	N/A
Type	Double Ended
UPC	883906398170

### Electrical

Current - Maximum per Contact	3.0A
Voltage - Maximum	30V AC/DC

### Physical

Cable Diameter	4.32mm (.170")
Cable Length	2.0m (6.56')
Color - Cable Jacket	Black
Connector End A	Nano-Change (M8)
Connector End B	Nano-Change (M8)
Coupling Style	Threaded
Gender	Female-Male
Keyway	None
LED Indicator	PNP Sensors
Material - Cable Jacket	PVC
Material - Connector Body	PVC
Material - Contact	Copper Alloy

Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Orientation	90° to Straight
Poles	3
Temperature Range - Operating	-25° to +80°C
Wire/Cable Type	UL 2464
Wire Size (AWG)	N/A

---

This document was generated on Mar 27, 2025