



Part Number : [1200980118](#)

Product Description : PROFIBUS Straight D-Sub Connector to Straight D-Sub Connector, 22 AWG, PUR Cable, 5.0m (16.40') Length

Series Number : 120098

Status : Active

Product Category : Circular Industrial Cordsets

Engineering Number : MM3S60PP4M050



Documents & Resources

Drawings

[1200980118_sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Reviewed per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Not Reviewed per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120098
Description	PROFIBUS Straight D-Sub Connector to Straight D-Sub Connector, 22 AWG, PUR Cable, 5.0m (16.40') Length
IP Rating	IP40
Product Name	PROFIBUS
Protocol	EtherNet
Type	Double Ended
UPC	78678886769

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Cable Diameter	8.00mm (.315")
Cable Length	5.0m (16.40')
Color - Cable Jacket	Violet
Connector End A	D-Sub (9-pin)
Connector End B	D-Sub (9-pin)
Coupling Style	Threaded
Gender	Male-Male
Keyway	None
LED Indicator	None
Material - Cable Jacket	PUR
Material - Connector Body	N/A
Material - Contact	N/A
Material - Coupling Nut	Gray Anodized Aluminum
Material - Plating Mating	N/A

Net Weight	428.291/g
Orientation	Straight to Straight
Poles	9
Temperature Range - Operating	0° to +60°C
Wire/Cable Type	Shielded-Twisted Pair
Wire Size (AWG)	22

This document was generated on Mar 27, 2025