



Part Number : [1202530349](#)

Product Description : Contrinex Inductive Sensor, 6.5mm Diameter Smooth Housing, 2mm Operating Distance, Embeddable, PNP, NC, 3-pin M8 Connector, 45mm Housing Length

Series Number : 120253

Status : Active

Product Category : Inductive and Photoelectric Sensors

Engineering Number : DW-AS-624-065-001




Documents & Resources

Specifications

[1202530342-000.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---------------------------------------------------------------------------------------|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Reviewed per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

| | |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Status | Active |
| Category | Inductive and Photoelectric Sensors |
| Series | 120253 |
| Description | Contrinex Inductive Sensor, 6.5mm Diameter Smooth Housing, 2mm Operating Distance, Embeddable, PNP, NC, 3-pin M8 Connector, 45mm Housing Length |
| IP Rating | IP67 |
| Product Name | Contrinex |
| Type | Inductive |
| UPC | 191130065547 |

Electrical

| | |
|---------------------|-----------|
| Output | NC |
| Polarity | PNP |
| Switching Frequency | ≤ 5000 Hz |

Physical

| | |
|-------------------------------|-----------------------|
| Connection | Connector (M8, 3-pin) |
| Length | 45mm |
| Material - Housing | Stainless Steel |
| Material - Sensing Face | PA12 |
| Mounting Style | Embeddable |
| Operating Distance | 2mm |
| Output | NC |
| Sensor Housing Size | 6.5mm dia. (smooth) |
| Temperature Range - Operating | -25° to +70°C |