



Part Number : [1202530555](#)

Product Description : Contrinex Inductive Sensor, M12 Fully Stainless Steel, 3mm Operating Distance, Embeddable, PNP, NO, 2m 3-wire PUR Cable, 50mm Housing Length

Series Number : 120253

Status : Active

Product Category : Inductive and Photoelectric Sensors

Engineering Number : DW-AD-703-M12



---

## Documents & Resources

### Specifications

[1202530553-000.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120253
Description	Contrinex Inductive Sensor, M12 Fully Stainless Steel, 3mm Operating Distance, Embeddable, PNP, NO, 2m 3-wire PUR Cable, 50mm Housing Length
IP Rating	IP68, IP69K
Product Name	Contrinex
Type	Inductive
UPC	191130069705

### Electrical

Output	NO
Polarity	PNP
Switching Frequency	≤ 600 Hz

### Physical

Connection	Cable (PUR 2m, 3-wire)
Length	50mm
Material - Housing	Stainless Steel
Material - Sensing Face	Stainless Steel
Mounting Style	Embeddable
Operating Distance	6mm
Output	NO
Sensor Housing Size	M12
Temperature Range - Operating	-25° to +85°C