



Part Number : [1202540003](#)

Product Description : Contrinex Photoelectric Sensor, C12 (13.5 x 21.8mm) Housing, Through-Beam (Receiver), 0 - 2000mm Operating Distance, NPN, Dark-ON, 0.2m 3-wire PVC Cable, 3-pin M8 Connector

Series Number : 120254

Status : Active

Product Category : Inductive and Photoelectric Sensors

Engineering Number : LLR-C12PA-NMV-302



Documents & Resources

Specifications

[1202540000-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, C12 (13.5 x 21.8mm) Housing, Through-Beam (Receiver), 0 - 2000mm Operating Distance, NPN, Dark-ON, 0.2m 3-wire PVC Cable, 3-pin M8 Connector
IP Rating	IP67
Operating Principle	Through-Beam (Receiver)
Product Name	Contrinex
Type	Photoelectric
UPC	191130066193

Electrical

Output	Dark-ON
Polarity	NPN
Switching Frequency	≤ 800 Hz

Physical

Connection	Cable (PVC 0.2m, 3-wire), Connector (M8, 3-pin)
Housing Size	13.5 x 21.8mm
Material - Housing	ABS
Material - Window	PMMA
Operating Distance	0 - 2000mm
Output	Dark-ON
Sensor Housing Size	C12
Temperature Range - Operating	-20° to +50°C