



**Part Number :** [1202540015](#)

**Product Description :** Contrinex Photoelectric Sensor, C12 (13.5 x 21.8mm) Housing, Background Suppression, 1 - 36mm Operating Distance, NPN, Light-ON, 2m 3-wire PVC Cable

**Series Number :** 120254

**Status :** Active

**Product Category :** Inductive and Photoelectric Sensors

**Engineering Number :** LHR-C12PA-NMK-301



---

## Documents & Resources

### Specifications

[1202540014-000.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, C12 (13.5 x 21.8mm) Housing, Background Suppression, 1 - 36mm Operating Distance, NPN, Light-ON, 2m 3-wire PVC Cable
IP Rating	IP67
Operating Principle	Background Suppression
Product Name	Contrinex
Type	Photoelectric
UPC	191130066513

### Electrical

Output	Light-ON
Polarity	NPN
Switching Frequency	≤ 800 Hz

### Physical

Connection	Cable (PVC 2m, 3-wire)
Housing Size	13.5 x 21.8mm
Material - Housing	ABS
Material - Window	PMMA
Operating Distance	1 - 36mm
Output	Light-ON
Sensor Housing Size	C12
Temperature Range - Operating	-20° to +50°C