



**Part Number :** [1202540079](#)

**Product Description :** Contrinex Photoelectric Sensor, 4mm Diameter Smooth Housing, Diffuse, 10mm Operating Distance, PNP, Light-ON, 3-pin M8 Connector, 45mm Housing Length

**Series Number :** 120254

**Status :** Active

**Product Category :** Inductive and Photoelectric Sensors

**Engineering Number :** LTR-D04MA-NSS-403



---

## Documents & Resources

### Specifications

[1202540076-000.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	Inductive and Photoelectric Sensors
Series	120254
Description	Contrinex Photoelectric Sensor, 4mm Diameter Smooth Housing, Diffuse, 10mm Operating Distance, PNP, Light-ON, 3-pin M8 Connector, 45mm Housing Length
IP Rating	IP67
Operating Principle	Diffuse
Product Name	Contrinex
Type	Photoelectric
UPC	191130067756

### Electrical

Output	Light-ON
Polarity	PNP
Switching Frequency	≤ 250 Hz

### Physical

Connection	Connector (M8, 3-pin)
Length	45mm
Material - Housing	Stainless Steel
Material - Window	Sapphire
Operating Distance	10mm
Output	Light-ON
Sensor Housing Size	4mm dia. (smooth)
Temperature Range - Operating	0° to +55°C