



**Part Number :** [1203410304](#)

**Product Description :** Micro-Change (M12) CAT6A Double-Ended Cordset, 8 Poles, X-Coded, Male (Straight) to Male (Straight), 26 AWG, Green Shielded PUR Cable, 4.0m (13.12') Length

**Series Number :** 120341

**Status :** Active

**Product Category :** Circular Industrial Cordsets

**Engineering Number :** E22E06020M040



---

## Documents & Resources

### Drawings

[1203410304\\_sd.pdf](#)

[PK-120341-300-001.pdf](#)


### Specifications

[PS-120341-001-001.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant  |
| China RoHS         |  |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21  |
| REACH SVHC         | Contains Lead per D(2024)7663-DC (21 Jan 2025)  |
| EU RoHS            | Compliant with Exemption 6(c) per EU 2015/863   |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

|                      |   |
|----------------------|---|
| Status               | Active  |
| Category             | Circular Industrial Cordsets  |
| Series               | 120341  |
| Description          | Micro-Change (M12) CAT6A Double-Ended Cordset, 8 Poles, X-Coded, Male (Straight) to Male (Straight), 26 AWG, Green Shielded PUR Cable, 4.0m (13.12') Length |
| IP Rating            | IP67  |
| Performance Category | 6A  |
| Product Name         | Micro-Change (M12) Cat6A, Industrial Ethernet   |
| Protocol             | EtherNet  |
| Type                 | Double Ended  |
| UPC                  | 884982411890  |

### Agency

|    |         |
|----|---------|
| UL | E361772 |
|----|---------|

### Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 0.5A |
| Voltage - Maximum             | 48V  |

### Physical

|                      |                    |
|----------------------|--------------------|
| Cable Diameter       | 6.90mm (.272")     |
| Cable Length         | 4.0m (13.12')      |
| Color - Cable Jacket | Green              |
| Connector End A      | Micro-Change (M12) |

|                               |                      |
|-------------------------------|----------------------|
| Connector End B               | Micro-Change (M12)   |
| Coupling Style                | Threaded             |
| Gender                        | Male-Male            |
| Keyway                        | X-Coded              |
| LED Indicator                 | None                 |
| Material - Cable Jacket       | PUR                  |
| Material - Connector Body     | PUR                  |
| Material - Contact            | Brass                |
| Material - Coupling Nut       | Nickel-plated Brass  |
| Material - Plating Mating     | Gold                 |
| Orientation                   | Straight to Straight |
| Poles                         | 8                    |
| Temperature Range - Operating | -20° to +80°C        |
| Wire/Cable Type               | Shielded PUR         |
| Wire Size (AWG)               | 26                   |