



Part Number : [1204000114](#)

Product Description : Ultra-Lock 2.0 (M12) Single-Ended Cordset, 12 Poles, A-Coded, Female (Straight) to Pigtail, PUR Cable, 5.0m Length

Series Number : 120400

Status : Active

Product Category : Circular Industrial Cordsets

Engineering Number : Y0C000H45M050



Documents & Resources

Drawings

[1204000114_sd.pdf](#)

Specifications

[1204000001-P10.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|--|
| GADSL/IMDS | Not Relevant |
| China RoHS | Not Relevant |
| EU ELV | Compliant with Exemption 3 per 2000/53/EC |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Contains Lead per D(2020)9139-DC (19 Jan 2021) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|--------------|--|
| Status | Active |
| Category | Circular Industrial Cordsets |
| Series | 120400 |
| Description | Ultra-Lock 2.0 (M12) Single-Ended Cordset, 12 Poles, A-Coded, Female (Straight) to Pigtail, PUR Cable, 5.0m Length |
| IP Rating | IP67 |
| Product Name | Ultra-Lock 2.0 (M12) |
| Type | Single Ended |
| UPC | 193264665358 |

Agency

| | |
|-----|--------|
| CSA | LR6837 |
|-----|--------|

Electrical

| | |
|-------------------------------|------|
| Current - Maximum per Contact | 1.5A |
| Voltage - Maximum | 30V |

Physical

| | |
|----------------------|----------------------|
| Cable Diameter | 6.00mm (.236") |
| Cable Length | 5.0m (16.40') |
| Color - Cable Jacket | Black |
| Connector End A | Ultra-Lock 2.0 (M12) |
| Connector End B | Pigtail |
| Coupling Style | Push to Lock |
| Gender | Female-Pigtail |
| Keyway | A-Coded |

| | |
|-------------------------------|---------------------|
| LED Indicator | None |
| Material - Cable Jacket | PUR |
| Material - Connector Body | TPU |
| Material - Contact | Brass |
| Material - Coupling Nut | N/A |
| Material - O-Ring | FPM |
| Material - Plating Mating | Gold |
| Net Weight | 223.513/g |
| Orientation | Straight to Pigtail |
| Poles | 12 |
| Temperature Range - Operating | -25❖❖ to +80°C |
| Wire/Cable Type | UL 20549, LS0H |
| Wire Size (AWG) | 26 |