



Part Number : [1204010016](#)

Product Description : Ultra-Lock 2.0 (M12) Double-Ended Cordset, 5 Poles, A-Coded, Female (Straight) to Male (Straight), PVC Cable, 10.0m Length

Series Number : 120401

Status : Active

Product Category : Circular Industrial Cordsets

Engineering Number : YY5030E03M100



Documents & Resources

Drawings

[1204010016_sd.pdf](#)

Specifications

[1204000001-P10.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|--|
| GADSL/IMDS | Not Relevant |
| China RoHS | Not Relevant |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Not Contained per D(2022)9120-DC (17 Jan 2023) |
| EU RoHS | Compliant per EU 2015/863 |

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|--------------|--|
| Status | Active |
| Category | Circular Industrial Cordsets |
| Series | 120401 |
| Description | Ultra-Lock 2.0 (M12) Double-Ended Cordset, 5 Poles, A-Coded, Female (Straight) to Male (Straight), PVC Cable, 10.0m Length |
| IP Rating | IP67 |
| Product Name | Ultra-Lock 2.0 (M12) |
| Type | Double Ended |
| UPC | 195842262430 |

Agency

| | |
|-----|--------|
| CSA | LR6837 |
|-----|--------|

Electrical

| | |
|-------------------------------|------|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 60V |

Physical

| | |
|----------------------|----------------------|
| Cable Diameter | 5.80mm (.230") |
| Cable Length | 10.0m (32.81') |
| Color - Cable Jacket | Black |
| Connector End A | Ultra-Lock 2.0 (M12) |
| Connector End B | Ultra-Lock 2.0 (M12) |
| Coupling Style | Push to Lock |
| Gender | Female-Male |
| Keyway | A-Coded |
| LED Indicator | None |

| | |
|-------------------------------|----------------------|
| Material - Cable Jacket | PVC |
| Material - Connector Body | TPC |
| Material - Contact | Brass, Copper Alloy |
| Material - Coupling Nut | N/A |
| Material - O-Ring | FPM |
| Material - Plating Mating | Gold |
| Net Weight | 527.937/g |
| Orientation | Straight to Straight |
| Poles | 5 |
| Temperature Range - Operating | -40° to +85°C |
| Wire/Cable Type | UL 2464 |
| Wire Size (AWG) | 22 |

This document was generated on Mar 27, 2025