



**Part Number :** [1204040008](#)


**Product Description :** Ultra-Lock 2.0 (M12) Receptacle, 8 Poles, Female (Straight), A-Coded, Back Panel Mount, M16 Mounting Threads, PCB Pins

**Series Number :** 120404

**Status :** Active

**Product Category :** Circular Industrial Connectors

**Engineering Number :** YR8U40000



---

## Documents & Resources

### Drawings

[1204040008\\_sd.pdf](#)

### Specifications

[1204000001-P10.pdf](#)

---

## Product Environment Compliance

### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## Part Details

### General

Status	Active
Category	Circular Industrial Connectors
Series	120404
Description	Ultra-Lock 2.0 (M12) Receptacle, 8 Poles, Female (Straight), A-Coded, Back Panel Mount, M16 Mounting Threads, PCB Pins
IP Rating	IP67, IP69K
Product Name	Ultra-Lock 2.0 (M12)
Type	PCB Mount
UPC	195842255715

### Electrical

Current - Maximum per Contact	2.0A
Voltage - Maximum	30V

### Physical

Coupling Type	Internal Thread   Push to Lock
Gender	Female
Keyway	A-Coded
Length	N/A
Material - Component	Nickel-plated Brass
Mounting Thread Size	M16
Orientation	Straight
Panel Mount	Back
Poles	8
Temperature Range - Operating	-40° to +85°C
Wire/Cable Type	UL 1569
Wire Size (AWG)	N/A

---

---

This document was generated on Mar 27, 2025