



**Part Number :** [1204061004](#)

**Product Description :** Ultra-Lock 2.0 (M12) Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male (Straight), EtherNet Cat5e TPE Cable, Teal, 1.0m Length

**Series Number :** 120406

**Status :** Active

**Product Category :** Circular Industrial Cordsets

**Engineering Number :** EYYA06004M010



---

## Documents & Resources

### Drawings

[1204061004\\_sd.pdf](#)

### Specifications

[1204000001-P10.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |              |
|--------------------|--------------|
| China RoHS         | Not Reviewed |
| EU ELV             | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC         | Not Reviewed |
| EU RoHS            | Not Reviewed |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## Part Details

### General

|                      |  |
|----------------------|--|
| Status               | Active   |
| Category             | Circular Industrial Cordsets   |
| Series               | 120406   |
| Description          | Ultra-Lock 2.0 (M12) Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male (Straight), EtherNet Cat5e TPE Cable, Teal, 1.0m Length |
| IP Rating            | IP67   |
| Performance Category | 5e   |
| Product Name         | Ultra-Lock 2.0 (M12),Industrial Ethernet   |
| Protocol             | EtherNet   |
| Type                 | Double Ended   |
| UPC                  | 195842328808   |

### Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 1.5A |
| Voltage - Maximum             | 60V  |

### Physical

|                           |                      |
|---------------------------|----------------------|
| Cable Diameter            | 6.50mm (.256")       |
| Cable Length              | 1.0m (3.28')         |
| Color - Cable Jacket      | Teal                 |
| Connector End A           | Ultra-Lock 2.0 (M12) |
| Connector End B           | Ultra-Lock 2.0 (M12) |
| Coupling Style            | Push to Lock         |
| Gender                    | Male-Male            |
| Keyway                    | D-Coded              |
| LED Indicator             | None                 |
| Material - Cable Jacket   | TPE                  |
| Material - Connector Body | TPC                  |

|                               |                      |
|-------------------------------|----------------------|
| Material - Contact            | Copper Alloy         |
| Material - Coupling Nut       | N/A                  |
| Material - Plating Mating     | Gold                 |
| Net Weight                    | 63.600/g             |
| Orientation                   | Straight to Straight |
| Poles                         | 4                    |
| Temperature Range - Operating | -40° to +85°C        |
| Wire/Cable Type               | TPE                  |
| Wire Size (AWG)               | 24                   |

---

This document was generated on Mar 27, 2025