



**Part Number :** [1210360833](#)

**Product Description :** Brad mPm DIN Form C-8mm to Micro-Change (M12) 5 Pole Cordset, C4 Circuit, Yellow LED, Male (90°) to Male (90°), 0.50mm<sup>2</sup> Black PUR Cable, 1.50m (4.92') Length, 24V

**Series Number :** 121036

**Status :** Obsolete

**Product Category :** Circular Industrial Cordsets

**Engineering Number :** H850B2P12M015



---

## Documents & Resources

---

### Product Environment Compliance

#### Compliance

GADSL/IMDS	Product not active
China RoHS	Product not active
EU ELV	Product not active
Low-Halogen Status	Product not active
REACH SVHC	Product not active
EU RoHS	Product not active

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Obsolete
Category	Circular Industrial Cordsets
Series	121036
Description	Brad mPm DIN Form C-8mm to Micro-Change (M12) 5 Pole Cordset, C4 Circuit, Yellow LED, Male (90°) to Male (90°), 0.50mm <sup>2</sup> Black PUR Cable, 1.50m (4.92') Length, 24V
IP Rating	IP65
Product Name	Micro-Change (M12),mPm
Protocol	N/A
Type	Double Ended
UPC	887191228211

### Electrical

Current - Maximum per Contact	1.5A
Voltage - Maximum	24V

### Physical

Cable Diameter	5.50mm (.216")
Cable Length	1.50m (4.92')
Color - Cable Jacket	Black
Connector End A	Brad mPm DIN C - 8mm
Connector End B	Micro-Change (M12)
Coupling Style	Threaded
Gender	Male-Male
Keyway	Single
LED Indicator	Yellow
Material - Cable Jacket	PUR
Material - Connector Body	Polypropylene
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - Plating Mating	Gold

Net Weight	105.000/g
Orientation	90° to 90°
Poles	5
Temperature Range - Operating	-25° to +75°C
Wire/Cable Type	PUR
Wire Size (AWG)	20

---

This document was generated on Mar 27, 2025