



Part Number : [1300170019](#)

Product Description : Mini-Change Field Attachable, Male Connector, 4 Pole, Cable Range: 5.08-11.43mm Outside Diameter with Internal Threads, Stainless Steel

Series Number : 130017

Status : Active

Product Category : Circular Industrial Connectors

Engineering Number : 1A4002-348




Documents & Resources

Drawings

[1300170019_sd.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|--------------|---|
| Status | Active |
| Category | Circular Industrial Connectors |
| Series | 130017 |
| Description | Mini-Change Field Attachable, Male Connector, 4 Pole, Cable Range: 5.08-11.43mm Outside Diameter with Internal Threads, Stainless Steel |
| Approvals | cCSAus certified |
| IP Rating | IP67 |
| Product Name | Mini-Change |
| Type | Field Attachable Connector |
| UPC | 78678853657 |

Agency

| | |
|-----|--------|
| CSA | LR6837 |
|-----|--------|

Electrical

| | |
|-------------------------------|------------|
| Current - Maximum per Contact | 13.0A |
| Voltage - Maximum | 600V AC/DC |

Physical

| | |
|---------------------------|---------------------------|
| Cable Diameter | 5.08-11.43mm (.200-.450") |
| Coupling Type | Internal Thread |
| Diagnostics / LEDs | No |
| Diagnostics Port | No |
| Gender | Male |
| Keyway | Single |
| Material - Connector Body | Nylon |
| Material - Contact | Copper Alloy |

| | |
|-------------------------------|--------------------------|
| Material - Coupling Nut | Stainless Steel Type 316 |
| Material - Plating Mating | Gold |
| Net Weight | 47.110/g |
| Orientation | Straight |
| Poles | 4 |
| Temperature Range - Operating | -20°C to +80°C |
| Wire Size (AWG) | 15 to 24 |

This document was generated on Mar 27, 2025