



Part Number : 1300850381

Product Description : Woodhead POW-R-MATIC Heavy Duty Cable Reel with Retraction Weight of 7lbs., 14/8 SOW, 27.43m (90.0') Cord Length with Flying Leads

Series Number : 130085

Status : Active

Product Category : Electrical Reels

Engineering Number : 92782



Product Environment Compliance

Compliance

| | |
|--------------------|--------------|
| China RoHS | Not Reviewed |
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------|------------------|
| Status | Active |
| Category | Electrical Reels |

| | |
|--------------------|--|
| Series | 130085 |
| Description | Woodhead POW-R-MATIC Heavy Duty Cable Reel with Retraction Weight of 7lbs., 14/8 SOW, 27.43m (90.0') Cord Length with Flying Leads |
| Comments | Applications: Vertical Lift, Drag, Recovery and Horizontal Stretch with 10% Sag. |
| Enclosure Rating | NEMA 3R |
| NEMA Configuration | N/A |
| Product Name | POW-R-MATIC |
| Type | Cable Reel |
| UPC | 78678879374 |

Agency

| | |
|-----|---------|
| CSA | LR29921 |
|-----|---------|

Electrical

| | |
|-------------------------------|------|
| Current - Maximum per Contact | 8.0A |
| GFCI | No |
| Lamp Wattage - Maximum | N/A |
| On/Off Switch | N/A |
| Voltage - Maximum | 600V |

Physical

| | |
|----------------|------------------|
| Bulb Included | N/A |
| Cable Length | N/A |
| Cable Movement | Ratchet Lock |
| Cord Length | 27.43m (90.0') |
| Cord Type | 14/8 SOW |
| Depth | 0.58m (22.750") |
| Drum Lock | Ratchet |
| Duty | Heavy |
| Guide Arm | Option Available |
| Height | 0.59m (23.38") |
| Lamp Type | N/A |

| | |
|--------------------------|-------------------|
| Material - Coating | Powder Coating |
| Material - Housing | Steel |
| Mounting Style | Rigid |
| Number of Conductors | 8 |
| Packaging Type | Carton |
| Primary Cord/Cable Entry | 1" NPT |
| Retraction Weight | 3.2kg (7.0 lb) |
| Width | 577.90mm (22.75") |
| Wire Size (AWG) | 14 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|---|--------------|
| Milli-Grid Dual Row Receptacle Housings | <u>51110</u> |
| Milli-Grid Vertical Through Hole PCB Receptacles | <u>78787</u> |
| Milli-Grid Top Entry Surface Mount PCB Receptacles | <u>78788</u> |
| Milli-Grid Vertical Through Hole PCB Receptacles | <u>79107</u> |
| Milli-Grid Vertical Through Hole PCB Receptacles | <u>79108</u> |
| Milli-Grid Top/Bottom Entry Surface Mount PCB Receptacles | <u>79109</u> |
| Milli-Grid Dual Row Cable-to-Board Receptacles | <u>87568</u> |