



**Part Number :** [1301530027](#)

**Product Description :** Super-Safeway In-Line Industrial GFCI, Portable, Single Phase, Manual Reset, Flying Lead Primary, TriTap Secondary (receptacle), 15A, 240V, 7.62m (25.0') Cord Length

**Series Number :** 130153

**Status :** Active

**Product Category :** Power Distribution

**Engineering Number :** 15050-25TTM



---

## Documents & Resources

### Drawings

[1301530027\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Relevant
EU ELV	Not Relevant
Low-Halogen Status	Not Relevant
REACH SVHC	Not Relevant
EU RoHS	Not Relevant

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	Power Distribution
Series	130153
Description	Super-Safeway In-Line Industrial GFCI, Portable, Single Phase, Manual Reset, Flying Lead Primary, TriTap Secondary (receptacle), 15A, 240V, 7.62m (25.0') Cord Length
Enclosure Rating	NEMA 3R
NEMA Configuration	NEMA 5-15
Product Name	Super-Safeway
Type	GFCI Industrial Duty, Single Phase
UPC	78678889755

### Agency

UL	E66308
----	--------

### Electrical

Current - Maximum per Contact	15.0A
GFCI	Yes-In-line
GFCI Reset	Manual
Ground Continuity Monitor	No
Open Neutral Relay	Yes
Voltage - Maximum	120V

### Physical

Cord Diameter	10.92mm (.430")
Cord Grip Body Size	Internal Double C-Clamp
Cord Length	15.24m (50.0')
Cord Type	12/3 SJTW
Feed-Thru	Yes
Flip Lid	No

Material - Housing	Nylon
Mounting Style	Portable
Number of Receptacles	1
Packaging Type	Carton
Receptacle Type	Single

---

This document was generated on Mar 27, 2025