



Part Number : [1301530095](#)

Product Description : Super-Safeway Right-Angle Industrial GFCI, Portable, Single Phase, Automatic Reset, Molded NEMA 5-15, 15A, 120V, 7.62m (25.0') Cord Length

Series Number : 130153

Status : Active

Product Category : Power Distribution

Engineering Number : 15054-25A



---

## Documents & Resources

### Drawings

[1301530095\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |              |
|--------------------|--------------|
| GADSL/IMDS         | Not Relevant |
| China RoHS         | Not Relevant |
| EU ELV             | Not Relevant |
| Low-Halogen Status | Not Relevant |
| REACH SVHC         | Not Relevant |
| EU RoHS            | Not Relevant |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

|                    |  |
|--------------------|--|
| Status             | Active   |
| Category           | Power Distribution   |
| Series             | 130153   |
| Description        | Super-Safeway Right-Angle Industrial GFCI, Portable, Single Phase, Automatic Reset, Molded NEMA 5-15, 15A, 120V, 7.62m (25.0') Cord Length |
| Enclosure Rating   | NEMA 3R  |
| NEMA Configuration | NEMA 5-15  |
| Product Name       | Super-Safeway  |
| Type               | GFCI Industrial Duty, Single Phase   |
| UPC                | 78678888267  |

### Agency

|    |        |
|----|--------|
| UL | E66308 |
|----|--------|

### Electrical

|                               |             |
|-------------------------------|-------------|
| Current - Maximum per Contact | 15.0A       |
| GFCI                          | Yes-In-line |
| GFCI Reset                    | Automatic   |
| Ground Continuity Monitor     | No          |
| Open Neutral Relay            | Yes         |
| Voltage - Maximum             | 125V        |

### Physical

|                     |                         |
|---------------------|-------------------------|
| Cord Diameter       | 10.92mm (.430")         |
| Cord Grip Body Size | Internal Double C-Clamp |
| Cord Length         | 7.62m (25.0')           |
| Cord Type           | 12/3 SJTW               |
| Feed-Thru           | Yes                     |
| Flip Lid            | No                      |
| Material - Housing  | Nylon                   |
| Mounting Style      | Portable                |

|                       |        |
|-----------------------|--------|
| Number of Receptacles | 0      |
| Packaging Type        | Carton |
| Receptacle Type       | N/A    |

---

This document was generated on Mar 27, 2025