



**Part Number :** [1301530135](#)

**Product Description :** Super-Safeway In-Line Industrial GFCI, IP69K, Portable, Single Phase, Manual Reset, Flying Leads (Primary), W-Splice to (3) NEMA 5-20 Watertite Extreme Receptacles (Secondary), 20A, 120V, 12/3 SJOOW Cord, 0.76m (2.5') Cord Length

**Series Number :** 130153

**Status :** Active

**Product Category :** Power Distribution

**Engineering Number :** 20052-W-2M



---

## Documents & Resources

### Drawings

[1301530135\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |              |
|--------------------|--------------|
| GADSL/IMDS         | Not Relevant |
| China RoHS         | Not Relevant |
| EU ELV             | Not Relevant |
| Low-Halogen Status | Not Relevant |
| REACH SVHC         | Not Relevant |
| EU RoHS            | Not Relevant |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

|                    |   |
|--------------------|---|
| Status             | Active  |
| Category           | Power Distribution  |
| Series             | 130153  |
| Description        | Super-Safeway In-Line Industrial GFCI, IP69K, Portable, Single Phase, Manual Reset, Flying Leads (Primary), W-Splice to (3) NEMA 5-20 Watertite Extreme Receptacles (Secondary), 20A, 120V, 12/3 SJOOW Cord, 0.76m (2.5') Cord Length |
| Enclosure Rating   | NEMA 4X   |
| NEMA Configuration | NEMA L5-20  |
| Product Name       | Super-Safeway   |
| Type               | GFCI Industrial Duty, Single Phase  |
| UPC                | 78678804610   |

### Electrical

|                               |             |
|-------------------------------|-------------|
| Current - Maximum per Contact | 20.0A       |
| GFCI                          | Yes-In-line |
| GFCI Reset                    | Manual      |
| Ground Continuity Monitor     | No          |
| Open Neutral Relay            | Yes         |
| Voltage - Maximum             | 120V        |

### Physical

|                     |                 |
|---------------------|-----------------|
| Cord Diameter       | 10.67mm (.420") |
| Cord Grip Body Size | N/A             |
| Cord Length         | 0.76m (2.5')    |
| Cord Type           | 12/3 SJOOW      |
| Feed-Thru           | Yes             |
| Flip Lid            | No              |
| Material - Housing  | Nylon           |
| Mounting Style      | Portable        |

|                       |              |
|-----------------------|--------------|
| Number of Receptacles | 3 - W-Splice |
| Packaging Type        | Carton       |
| Receptacle Type       | GFCI Triple  |

---

This document was generated on Mar 27, 2025