



Part Number : 1302261856

Product Description : Heavy Duty Stranded Cable, Rubber, 18 AWG, 8 Conductors, 304.80mm Length, Black

Series Number : 130226

Status : Active

Product Category : Industrial Cable

Engineering Number : R62210116

Image coming soon

---

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant                                  |
| China RoHS         | Not Relevant                                  |
| EU ELV             | Not Relevant                                  |
| Low-Halogen Status | Not Relevant                                  |
| REACH SVHC         | Not Reviewed per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS            | Not Relevant                                  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

|        |        |
|--------|--------|
| Status | Active |
|--------|--------|

|              |   |
|--------------|---|
| Category     | Industrial Cable  |
| Series       | 130226  |
| Description  | Heavy Duty Stranded Cable, Rubber, 18 AWG, 8 Conductors, 304.80mm Length, Black |
| Product Name | Heavy Duty  |
| UPC          | 78678864169   |

### Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 4.9A |
| Voltage - Maximum             | 600V |

### Physical

|                               |               |
|-------------------------------|---------------|
| Cable Length                  | 304.80mm      |
| Circuits (Loaded)             | 8             |
| Color - Cable Jacket          | Black         |
| Net Weight                    | 38.101/g      |
| Outer Jacket Diameter         | 10.99mm       |
| Packaging Type                | Carton        |
| Temperature Range - Operating | -40° to +75°C |
| Wire/Cable Type               | Rubber        |
| Wire Size (AWG)               | 18            |