



**Part Number :** [1552200072](#)


**Product Description :** Flamar Sensor Cable, WSOR Jacket, Unshielded, 4 Circuits, 0.34mm<sup>2</sup> / 22 AWG, 5.10mm (.201") Diameter, 1500.0m (4921.26') Length, Yellow

**Series Number :** 307963

**Status :** Active

**Product Category :** Industrial Cable

**Engineering Number :** B55-4-1X1500M



---

## Documents & Resources

### Specifications

[1552200001-P1E.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	Industrial Cable
Series	307963
Description	Flamar Sensor Cable, WSOR Jacket, Unshielded, 4 Circuits, 0.34mm <sup>2</sup> / 22 AWG, 5.10mm (.201") Diameter, 1500.0m (4921.26') Length, Yellow
Geographic Area	Global
Product Name	Flamar,Signal and Control
UPC	889056458061

### Agency

UL	E172949
----	---------

### Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V

### Physical

Bending Radius - Minimum	> 7.5xOD
Cable Length	1500.0m
Circuits (Loaded)	4
Color - Cable Jacket	Yellow
Insulation	TPE
Material - Outer Jacket	WSOR
Net Weight	0.036/kg
Outer Jacket Diameter	5.10mm
Packaging Type	Reel
Temperature Range - Operating	-25° to +80°C
Wire/Cable Type	UL AWM 21215 / CSA
Wire Size (AWG)	22
Wire Size mm <sup>2</sup>	0.34

---

**Use with Part(s)**

Description	Part Number
Micro-Change (M12) Field Attachable Connectors	<u>120071</u>
Ultra-Lock (M12) Single Keyway Field Attachable Connectors	<u>120085</u>
Nano-Change (M8) Field Attachable Connectors	<u>120091</u>

---

This document was generated on Mar 27, 2025