



Part Number : [1553319009](#)

Product Description : Flamar Feedback Cable, PUR Jacket, Braided Shielding Overall, 12 Circuits, 4x(2x0.34mm²) + 4x(0.50mm²) / 4x(2x22 AWG) + 4x(21 AWG), 9.50mm (.374") Diameter, 1000.0m (3280.83') Length, Green

Series Number : 307965

Status : Active

Product Category : Industrial Cable

Engineering Number : 1X1000M



Documents & Resources

Specifications

[1553319001-P1E.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

Status	Active
Category	Industrial Cable
Series	307965
Description	Flamar Feedback Cable, PUR Jacket, Braided Shielding Overall, 12 Circuits, 4x(2x0.34mm ²) + 4x(0.50mm ²) / 4x(2x22 AWG) + 4x(21 AWG), 9.50mm (.374") Diameter, 1000.0m (3280.83') Length, Green
Geographic Area	Global
Product Name	Flamar,Servo Motor
UPC	889056462150

Agency

UL	E172949
----	---------

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	1000V

Physical

Bending Radius - Minimum	> 10xOD
Cable Length	1000.0m
Circuits (Loaded)	12 (8+4)
Color - Cable Jacket	Green
Insulation	TPE
Material - Outer Jacket	PUR
Net Weight	0.119/kg
Outer Jacket Diameter	9.50mm
Packaging Type	Reel
Temperature Range - Operating	-40° to +80°C
Wire/Cable Type	UL AWM 21223 / CSA

Wire Size (AWG)	21, 22
Wire Size mm ²	0.34, 0.50

Use with Part(s)

Description	Part Number
Brad M23 Signal Connectors	<u>120230</u>
Brad M23 Signal Connectors	<u>120233</u>

This document was generated on Mar 27, 2025