



Part Number : [1554111004](#)


Product Description : Flamar PROFIBUS DP Network Cable, PVC Jacket, Braided Shielding Overall, 2 Circuits, 0.34mm² / 22 AWG, 8.20mm (.323") Diameter, 200.0m (656.17') Length, Violet

Series Number : 307964

Status : Active

Product Category : Industrial Cable

Engineering Number : 1X200M



Documents & Resources

Specifications

[1554111004-P1E.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Contained per D(2022)4187-DC (10 June 2022)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

Status	Active
Category	Industrial Cable
Series	307964
Description	Flamar PROFIBUS DP Network Cable, PVC Jacket, Braided Shielding Overall, 2 Circuits, 0.34mm ² / 22 AWG, 8.20mm (.323") Diameter, 200.0m (656.17') Length, Violet
Geographic Area	Global
Product Name	Flamar,Network
Protocol	PROFIBUS
UPC	889056462600

Agency

UL	E172949
----	---------

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	300V

Physical

Bending Radius - Minimum	> 15xOD
Cable Length	200.0m
Circuits (Loaded)	2
Color - Cable Jacket	Violet
Insulation	Foam PE
Material - Outer Jacket	PVC
Net Weight	0.078/kg
Outer Jacket Diameter	8.20mm
Packaging Type	Reel
Temperature Range - Operating	+5° to +60°C
Wire/Cable Type	UL AWM 2464 / CSA

Wire Size (AWG)	22
Wire Size mm ²	0.34

Use with Part(s)

Description	Part Number
Brad M23 Signal Connectors	<u>120230</u>
Brad M23 Signal Connectors	<u>120233</u>

This document was generated on Mar 27, 2025