



Part Number : 1554216012

Product Description : Flamar Ethernet 5e Network Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(2x0.25mm<sup>2</sup>) / 4x(2x24 AWG), 7.80mm (.307") Diameter, 1000.0m (3280.83') Length, Teal

Series Number : 307964

Status : Active

Product Category : Industrial Cable

Engineering Number : 1X1000M



---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
--------	--------

Category	Industrial Cable
Series	307964
Description	Flamar Ethernet 5e Network Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(2x0.25mm <sup>2</sup> ) / 4x(2x24 AWG), 7.80mm (.307") Diameter, 1000.0m (3280.83') Length, Teal
Geographic Area	Global
Product Name	Flamar,Network
Protocol	EtherNet 5e
UPC	889056465120

#### Agency

UL	E172949
----	---------

#### Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V

#### Physical

Bending Radius - Minimum	> 15xOD
Cable Length	1000.0m
Circuits (Loaded)	8
Color - Cable Jacket	Teal
Insulation	PE
Material - Outer Jacket	WSOR
Net Weight	0.073/kg
Outer Jacket Diameter	7.80mm
Packaging Type	Reel
Temperature Range - Operating	-10° to +60°C
Wire/Cable Type	UL AWM 21215 / CSA
Wire Size (AWG)	24
Wire Size mm <sup>2</sup>	0.25

---

Use with Part(s)

Description	Part Number
Micro-Change (M12) Field Attachable Connectors	<u>120071</u>
Micro-Change (M12) Field Attachable Connectors and D-Sub Connectors	<u>120100</u>
Micro-Change (M12) and Mini-Change Trunk and Drop Connectors	<u>130034</u>
Field Attachable Connectors	<u>130047</u>

---

This document was generated on Mar 27, 2025